



DEFENDER[®]

ROOF EDGE PROTECTION



DEFENDER ROOF EDGE PROTECTION systems are freestanding, with no requirement for fixings or drilling and subsequently no repair to the roof membrane, suitable for flat roofs up to 3° pitch.

The systems can be configured to satisfy the requirements of BS EN ISO 14122 part 3 or the load and deflection requirements of BS EN 13374 Class A.

DEFENDER ROOF EDGE PROTECTION systems operate on a counterbalance principle using curved PVC counterweights as the main component. A galvanised malleable iron foot with a protective rubber base supports the handrail post; this includes an integral toeplate facility which is a fundamental requirement if there is no perimeter edge upstand.

All systems feature 1100mm tall factory pre-assembled uprights that include open cradle fittings allowing the handrail tube to be quickly dropped into place instead of the time consuming process of being fed through several fittings as required with other systems, speeding up assembly and saving cost.



ECONOMY SYSTEM

A simple and cost effective way of protecting roof edges.

RE00G40 Uprights are positioned to a **maximum** bay size of 2.8m and RE11P40 counterweights (overall length 1942mm) are fitted on every other upright post to a **maximum** distance 5.6m*



STANDARD SYSTEM

Shorter length counterweight tubes, enables installation in restricted roof areas.

RE00G40 upright posts each fitted with RE1140SS counterweight assemblies (1442mm overall length) **maximum** bay sizes of 2.8m*



PLUS SYSTEM

Aesthetically pleasing, curved uprights with 3 rails for added security.

RE00G40SS upright posts placed at **maximum** bay sizes of 2.8m fitted with RE1140SS counterweight assemblies (1442mm overall length) on every other upright post **maximum** bay sizes of 5.6m*

*Maximum bay size dependant on roof configuration and compliance standard requirements.

Benefits

- System is effectively maintenance free with hot dip galvanised fittings and tube to BS EN ISO 1461
- Recycled PVC counterweights
- For use on asphalt, coated steel sheeted, concrete or mineral felt roofs
- Rapid installation, no special tools or specialised labour required
- No on site welding or bending required
- Base fitting allows option of installing uprights up to 11° from vertical
- Bolt on toeplate available to comply with HSG 33.

System Components

RE00G40
Pre-assembled
Upright

48mm dia,
1100mm high



Used for Economy
and Standard systems

RE00G40SS
Pre-assembled
Curved Upright

48mm dia,
1100mm high



Used for
Plus system

C00G40
Sleeve Joint



Used to connect adjoining
handrail sections together.

C02G40 90°
Elbow



Used to change direction at
90° without bending the tube
or to form D return end.

C05G40
Variable Elbow



Used to make joints at an
angle of between 15° and
60° without bending the
tube.

C11G40
Wall Flange



Allows ends of systems to
be structurally fixed.

RE11P40SS



Intermediate counterweight assembly
comprising PVC Weight, locking
collar, 42 mm dia tube 1000mm long.
Used for Standard and Plus systems.

RE11P40



Intermediate counterweight assembly
comprising PVC Weight, locking
collar, 42 mm dia tube 1575mm long.
Used for Economy system.

RE12P40




Run-end counterweight assembly,
used on all systems with a 'free end'.
Containing 2no PVC weights, 2no
locking collars, 1no solid 690mm bar
and 42 dia tube 1575mm long.
Supplied loose for site assembly.

DEFENDER ROOF EDGE PROTECTION • ECONOMY • STANDARD • PLUS

Access Technologies Ltd

Cradley Business Park,
Overend Road, Cradley Heath,
West Midlands B64 7DW



DEFENDER
ROOF EDGE PROTECTION

Tel: +44 (0)1384 632387

Fax: +44 (0)1384 632384

Email: sales@defendertuv.co.uk

Internet: www.defendertuv.co.uk

DEFENDER ROOF EDGE PROTECTION is a registered trademark of Access Technologies Limited. Whilst every effort has been made to ensure the accuracy of the information contained in this brochure, Access Technologies Ltd cannot be held responsible for any errors or omissions. Access Technologies Ltd reserves the right to alter or withdraw products without prior notice. Access Technologies Ltd accepts no responsibility for any loss or damage arising from improper use of their products. No part of this brochure may be reproduced in any form without prior permission in writing from Access Technologies Ltd. © 2012 Access Technologies Limited. All Rights Reserved